



**PROTEK**  
CONCRETE RESURFACING

## DID YOU APPRECIATE **YOUR EXPERIENCE ?**

*We invite you to share your opinion on  
our Google and Facebook pages*



[facebook.com/bprotek/](https://facebook.com/bprotek/)



Look for your local franchisee on  
Google and Google Maps and give  
feedback from your Gmail account.



**PROTEK**  
CONCRETE RESURFACING

## MAINTENANCE GUIDE

*For Your Polyaspartic  
Or Epoxy Floors*



[WWW.BPROTEK.COM](http://WWW.BPROTEK.COM)

## POLYASPARTIC WITH FLAKES

- 

Mix a delicate neutral PH soap with water.
- 

Lather the soap mixture onto the surface using a floor brush with plastic bristles.
- 

Rinse with plenty of water (a pressure washer may be used 12 inches from the surface at a maximum of 1 200 psi).
- 

Remove as much water as possible using a squeegee and let the surface dry.

### Tips

- To prevent damaging the surface, clean up all spills (oil and gas included) as soon as they occur.
- Tough stains : Use a degreaser soap in stained or heavily soiled areas. (Careful : strong cleaners may damage the surface's luster)

### Caution

- Minimize the possibility of scratches and marks that could occur when moving furniture, equipment, goods, studded tires, etc.
- You may use light abrasive materials such as salt and sand on the surface.
- Outdoors, only use a plastic shovel, as a metal shovel may damage the surface.

## EPOXY

- 

Remove dirt and dust using a soft bristle brush or a vacuum cleaner.
- 

Wash the floor using a mop and a delicate neutral PH soap with water.
- 

Rinse with water.
- 

Wipe the surface with a clean and dry cloth or a microfiber.

### Tips

- A sweeping cloth like a "Swiffer" is ideal for the daily maintenance of your surface.
- To protect your epoxy floor, take the same precautions as with a wooden floor. Use protective pads under chair legs, tables and furniture.
- Over time, the luster of an epoxy fades. You can apply a coat of wax to preserve its glossy finish.

### Caution

- **Wait 7 days after installation** before washing the floor.
- Minimize the possibility of scratches and marks that could occur when moving furniture, office chairs, stools etc.
- Avoid hard bristle brushes or abrasive cleaning tools and solutions.